

K2015 *"Micro with the highest functionality & specifications"* Ambient Model

- Speed** 500-15000Rpm
in 1 Rpm steps
- Max Rcf** 22000G
- Timer** 0-999Minutes + hold
in 1 second steps
- Dims HWD** 27x33x46Cms
- Weight** 16.5Kilos
without rotor



K2015R *"The micro chill..."* Refrigerated Model

- Speed** 500-15000Rpm
in 1 Rpm steps
- Max Rcf** 22000G
- Timer** 0-999Minutes
+ hold in
1 second steps
- Dims HWD** 35x40x62Cms
- Weight** 45Kilos
without rotor
- Temp** -9 to +40C PID Controlled
accuracy and control to 0.5C



Rotors - fixed angle available to both



BRK5424

Reducers available

max speed 15000 Rpm 22,000G
24 x 1.5-2.2ml tube, fixed angle rotor
Tube size maximum H40 x W11mm
0.2 - 0.4ml and 0.5ml



BRK5436

max speed 15000 Rpm 22,000G
36 x 0.5ml tube, fixed angle rotor
Tube size maximum H40 x W8mm

BRK5448

48 x 0.2ml tube, fixed angle rotor
Tube size maximum H40 x W6mm



BRK5494

max speed 15000 Rpm 22,000G
4 x 8 place strip PCR tubes (0.2ml)



BRK5308

Reducers available

max speed 6000 Rpm 4,800G
8 x 50ml tube, fixed angle rotor
Tube size maximum H115 x W30mm
15ml and 25ml



BRK5324

Reducers available

max speed 6000 Rpm 4,800G
24 x 15ml tube, fixed angle rotor
Tube size maximum H120 x W17 mm
5ml and 10ml